



## K-TEC 1237 ADT TRAIN

Using a single power unit and one operator, the K-Tec 1237ADT Train doubles up efficiency by pulling two 1237 scrapers. On job sites with longer cut-zone and haul road areas, a massive advantage is gained to provide a tandem heaped capacity of 74 cubic yards / 56.6 cubic metres. The 1237ADT Train provides impressive production performance at the end of the day. This configuration has an added advantage since it can split into singles on your job site as conditions change.



## K-TEC 1237 ADT TRAIN SCRAPER FEATURES




## 1237 ADT TRAIN SPECIFICATIONS

| General Specifications          | Standard                                    | Metric                          |
|---------------------------------|---|---------------------------------|
| Heaped Capacity (ISO)           | 74 Cubic Yards                              | 56.57 Cubic Metres              |
| Struck Capacity                 | 40.5 Cubic Yards                            | 30.9 Cubic Metres               |
| Max Loading Rating              | 176,000 lbs                                 | 79,832 kgs                      |
| Bucket Dimensions               | 12' W x 4' 3" H x 12' 10" L                 | 3.66m W x 1.29m H x 3.91m L     |
| Cutting Width                   | 12'   | 3.66m                           |
| Cutting Edge                    | 3-Piece Blade                               | 3-Piece Blade                   |
| Gate Opening                    | 6' 8"                                       | 2.03m                           |
| Turning Radius                  | 33'   | 10m                             |
| Gate Cylinders                  | 5" x 26"                                    | 127mm x 660mm                   |
| Lift Cylinders                  | 5.5" x 32"                                  | 140mm x 813mm                   |
| Ejector Cylinder                | 5.5" x 76"                                  | 140mm x 1,930mm                 |
| Cutting Edge Clearance          | 28"   | 0.71m                           |
| Ball to Rear Axle Length        | 28' 9"                                      | 8.77m                           |
| Rack Height (Tilttable)         | 4'  | 1.22m                           |
| Weight Distribution             | 30% Hitch, 70% Scraper Axle                 | 30% Hitch, 70% Scraper Axle     |
| 8 Tires                         | 26.5 R25 Radial                             | 26.5 R25 Radial                 |
| Horsepower Required             | 450 HP +                                    | 330 kW +                        |
| Wrap Around Mud Scrapers        | Standard                                    | Standard                        |
| Gate Extension                  | Standard                                    | Standard                        |
| Lead Scraper Structural Package | Tie Rods, Tail Hitch, Rack Ext.             | Tie Rods, Tail Hitch, Rack Ext. |
| Truck Fender & Catwalk System   | Standard                                    | Standard                        |
| Transport Dimensions            | Standard                                    | Metric                          |
| Overall Width                   | 14'   | 4.27m                           |
| Overall Height                  | 11' 1", 10'                                 | 3.4m, 3.04m                     |
| Overall Length                  | 36' 6", 36' 6"                              | 11.13m, 11.13m                  |
| Shipping Weight                 | 41,570 lbs, 39,130 lbs                      | 18,855 kgs, 17,749 kgs          |
| Overseas Shipping               | 40' Highcube Container (2)                  | 40' Highcube Container (2)      |
| Optional Upgrades               |   |                                 |
| Brake System                    | 4 or 8 Caliper Disc System                  |                                 |
| Height Gauge                    | Increases cutting depth visibility          |                                 |
| Mine Version                    | Heavier plate steel for mining applications |                                 |

Specifications are subject to change without notice.



## RECOMMENDED POWER UNIT



450HP +/330 KW +  
Articulated Dump Truck