

Maximizer 2B Asphalt Distributor

Rosco
A **LeeBoy** Company



Applying a tack coat requires a sophisticated piece of equipment like the Maximizer 2B to ensure a uniform spray. The folding spray bar allows application without extensions and easily adjusts to provide even coverage of triple overlap fan spray pattern. Trusting in the proven reliability and solid performance that can only be found in a Viking asphalt pump coupled with our proprietary spraying algorithms, the Maximizer 2B yields long-lasting, top notch performance for all application types.

Performance Features:

- 12' Fully Circulating Folding Spraybar
- Application Without Extensions
- Automatic In-Cab Controls
- Internal Spraybar Valves
- 400 Gallons Per Minute Viking Asphalt Pump
- Enviro-Flush Clean Out System
- Accurate Application Regardless of Spraybar Width or Spraying Speed
- 12 Presets for Application Rate
- Radar Horn Speed and Distance Monitoring



Max 2B Asphalt Distributor Specifications



<p>Tank Capacity</p> <ul style="list-style-type: none"> - 1,050 gallons to 5,313 gallons * Gallons listed are maximum tank capacities. Recommended tank capacities may be limited by 1.) Thermal expansion of materials. 2.) Density of materials. 3.) Truck/axle load ratings. For more detail, please contact your local Rosco Sales Representative or Dealer. 	<ul style="list-style-type: none"> - Capable of storing up to 12 preset application rates for instant retrieval - Readouts include FPM, GPM, total feet sprayed, total gallons sprayed, total sq. yards sprayed, flow and speed calibration, application rate, tank temperature, hour meter, spraybar width
<p>Tank</p> <ul style="list-style-type: none"> - Meets all applicable Federal DOT regulations - 10 gauge steel shell - 7 gauge steel reinforced, flanged heads - Seams are electrically welded 	<p>Additional Standard Equipment</p> <ul style="list-style-type: none"> - Hand spray wand with a 25' rubber hose - Front and rear dial contents gauge - 4" dial, internal pencil thermometers - Sample valve - Back up alarm - Ladder and platform assembly
<p>Insulation</p> <ul style="list-style-type: none"> - 2" rock wool with spacers to prevent compression - Protected by an aluminium jacket 	<p>Optional Equipment</p> <ul style="list-style-type: none"> - Installation for a customer supplied truck chassis - PTO transmission (required if not using front live power) - LPG burner, includes 48 gallon LP tank - LPG burners with electronic ignition, 100% outfire protection and heat control - Diesel burners with outfire protection and heat limit control - Heated asphalt pump - Emulsion tank hand railing, electric actuated - Washdown system with pump and hose, self-winding hose reel - Spraybar extensions, 1' lengths (max 4 each) - Spraybar extensions, 2' lengths (max 2 each) - Loading hose, 3" x 15' flexible steel with quick couplers - Loading hose, 3" x 15' rubber with quick couplers - LED working lights, qty 4 - Additional toolboxes, depends on framerrail availability - Electric overnight heat, 240V single phase - GPS speed sensor in lieu of Radar Horn speed sensor - Other options available, visit LeeBoy.com
<p>Heat System</p> <ul style="list-style-type: none"> - Two diesel fired burners with electric ignition - 560,000 BTU per burner, per hour capacity 	
<p>Asphalt Pump</p> <ul style="list-style-type: none"> - Viking, positive displacement pump - 400 gallon per minute 	
<p>Clean Out</p> <ul style="list-style-type: none"> - Enviro-flush allows circulation through asphalt pump, valves, distributing lines and spraybar - Material returned to tank for later use or disposal - 25 gallons capacity 	
<p>Spraybar</p> <ul style="list-style-type: none"> - Exclusive two-way spraybar breakaway system - Safety relieving feature provides protection if an obstruction is hit in either forward or reverse - Brass, slotted nozzles and valves are non-clogging - Quick-disconnect allows operator to change spray widths in 4" increments - 12' full circulating bar - Two 4' center sections - Two 2' hydraulic folding spraybar wings - Nozzles: spaced 4" centers on spraybar - Spraybar shifts 18" each way 	
<p>Operator's In-Cab Controls</p> <ul style="list-style-type: none"> - Plus+1 CAN Bus control and onboard diagnostics - 7" 800 x 480, high-res color display - Automatic application rate control - Settings for flow, speed calibration, spraybar width, spraybar on/off control by section 	



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com



LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-70016-EN